

Inference Trees: Adaptive Inference with Exploration

Tom Rainforth¹ Yuan Zhou¹ Xiaoyu Lu¹ Yee Whye Teh¹ Frank Wood¹ Hongseok Yang² Jan-Willem van de Meent³

¹University of Oxford; ²KAIST, South Korea; ³Northeastern University



Overview

- Inference trees (ITs) are a new adaptive Monte Carlo inference method building on ideas from Monte Carlo tree search (MCTS)
- Existing adaptive inference methods are implicitly based on pure exploitation, ITs explicitly aim to balance exploration and exploitation
- ITs use bandit strategies to adaptively sample from hierarchical partitions of the space, while simultaneously learning these partitions
- Particularly effective in combination with sequential Monte Carlo (SMC)

Take Home

- By explicitly allocating computational resources to exploration, we can construct more efficient and robust methods for adaptive inference
- Can capture long range dependencies and potentially improve beyond what can be achieved by proposal adaption alone in SMC


Partitioning the Target Space

- Aim: approximate posterior $p(x_{1:T}|Y)$, $x_{1:T} \in \mathbb{X}_T$
- We partition $\mathbb{X}_T$ into separate regions $\{A_i\}_{i \in \mathcal{I}}$
- Run inference separately on each region, e.g. using SMC, then combine
- Allocate computational resources using MCTS
- Partitioning $\mathbb{X}_T$ directly is difficult $\Rightarrow$ partition in cumulative space $\mathbb{Z}_T$

$$z_t = \eta_t(x_t; x_{1:t-1}) = \int_{-\infty}^{x_t} q_t(x'_t | x_{1:t-1}) dx'_t \quad (1)$$

$$q_{i,t}(x_t | x_{1:t-1}, \{z_t \in Z_{i,t}\}) = \frac{q_t(x_t | x_{1:t-1}) \mathbb{I}(z_t \in Z_{i,t})}{\int_0^1 \mathbb{I}(z_t \in Z_{i,t}) dz_t} \quad (2)$$

- Using orthogonal partitioning of $\mathbb{Z}_T$: $B_1, B_2, \dots, B_T$
- This implies a non-orthogonal partitioning of $\mathbb{X}_T$: $A_1, A_2, \dots, A_T$



Combining Estimates

- Estimates from different partitions combined in an unweighted fashion

$$\begin{aligned} \mathbb{E}_{p(x_{1:T}|Y)}[f(x_{1:T})] &= \frac{1}{p(Y)} \int p(x_{1:T}, Y) f(x_{1:T}) dx_{1:T} \\ &= \frac{1}{p(Y)} \sum_{i \in \mathcal{I}} \mathbb{E}_{Q(x_{1:T} | \{z_{1:T} \in B_i\})} \left[\frac{p(x_{1:T}, Y) f(x_{1:T}) \prod_{t=1}^T \mathbb{I}(z_t \in Z_{i,t})}{Q(x_{1:T} | \{z_{1:T} \in B_i\})} \right] \\ &\approx \frac{\sum_{i \in \mathcal{I}} \hat{Q}_i}{\sum_{i \in \mathcal{I}} \hat{V}_i} \quad \text{where} \quad \hat{Q}_i = \frac{1}{N_i} \sum_{n=1}^{N_i} w_n^i f(\hat{x}_{1:T,i}^n), \quad \hat{V}_i = \frac{1}{N_i} \sum_{n=1}^{N_i} w_n^i \end{aligned}$$

- Node estimate is combination of local estimate and children


$$\hat{\mu}_j = \frac{c_j - (c_{l_j} + c_{r_j})}{c_j} \hat{Q}_j + \frac{c_{l_j} + c_{r_j}}{c_j} (\hat{\mu}_{l_j} + \hat{\mu}_{r_j}) \quad (3)$$

Tree Learning Algorithm


Three key components to training:

- **Traversal** – Choose a node to update using upper confidence bounding. This adaptively allocates resources to where they are needed.
- **Refinement** – Either run inference at chosen node or split it and run inference for children. The latter uses the existing samples at the node to choose a good split
- **Propagation** – Update the tree with information from new estimates.


Traversal



Refinement



Propagation




Consistent Regardless of Training Strategy

Consistent regardless of training strategy given some weak assumptions

- Assumption 1 – individual estimators converge
- Assumption 2 – nodes sampled from infinitely often if sibling is also
- Assumption 3 – depth of tree remains bounded

Theorem 1. *If Assumptions 1, 2, and 3 hold, then all estimates calculated using an IT converge weakly as $K \rightarrow \infty$.*

Experimental Results



References

- [1] James Neufeld, Andras Gyorgy, Csaba Szepesvari, and Dale Schuurmans. Adaptive Monte Carlo via Bandit Allocation. In *Proceedings of the 31st International Conference on Machine Learning*, volume 32, pages 1944–1952, 2014.
- [2] Alexandra Carpentier, Remi Munos, and András Antos. Adaptive Strategy for Stratified Monte Carlo Sampling. *Journal of Machine Learning Research*, 16:2231–2271, 2015.

Acknowledgements

- BP, ESPRC, DARPA, MSIP