

Disentangled Dynamic Representations from Unordered Data

Leonhard Helming¹ Abdelaziz Djelouah Markus Gross¹ Romann M. Weber

¹ETH Zurich

Motivation

- Better interpretability through disentangled representation
- In context of video: static and dynamic information
- Pairwise comparison instead of recurrent architecture

Contribution

We introduce a deep generative model that learns disentangled static and dynamic representations from data without temporal ordering

Model

Generative Model:


$$p_{\theta}(\mathbf{x}_{1:T}, \mathbf{f}, \mathbf{z}_{1:T}) = p_{\theta}(\mathbf{f}) \prod_{t=1}^T p_{\theta}(\mathbf{x}_t | \mathbf{f}, \mathbf{z}_t) p_{\theta}(\mathbf{z}_t | \mathbf{f})$$

Inference Model:

$$q_{\phi}(\mathbf{f}, \mathbf{z}_{1:N} | \mathbf{x}_S) = q_{\phi}(\mathbf{f} | \mathbf{x}_S) \prod_{i=1}^N q_{\phi}(\mathbf{z}_{s_i} | \mathbf{f}, \mathbf{x}_{s_i})$$

Learning:

$$\mathcal{L} = \mathbb{E}_{q_{\phi}(\mathbf{f} | \mathbf{x}_S)} \left[\sum_{\mathbf{x} \in \mathbf{x}_S} \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{f}, \mathbf{x})} [\log p_{\theta}(\mathbf{x} | \mathbf{f}, \mathbf{z}) - \text{D}_{KL}(q_{\phi}(\mathbf{z} | \mathbf{f}, \mathbf{x}) || p_{\theta}(\mathbf{z} | \mathbf{f}))] \right] - \text{D}_{KL}(q_{\phi}(\mathbf{f} | \mathbf{x}_S) || p_{\theta}(\mathbf{f}))$$



Distributions of the generative model:

$$p_{\theta}(\mathbf{f}) = \mathcal{N}(\mathbf{f} | \mathbf{0}, \mathbf{1}),$$

$$p_{\theta}(\mathbf{z} | \mathbf{f}) = \mathcal{N}(\mathbf{z} | h_{\mu_z}(\mathbf{f}), \text{diag}(h_{\sigma_z^2}(\mathbf{f})))$$

$$p_{\theta}(\mathbf{x} | \mathbf{f}, \mathbf{z}) = \text{Ber}_p(\mathbf{x} | h_x(\mathbf{f}, \mathbf{z}))$$



Distributions of the inference model:

$$q_{\phi}(\mathbf{f} | \mathbf{x}_S) = \mathcal{N}(\mathbf{f} | g_{\mu_f}(\mathbf{x}_S), \text{diag}(g_{\sigma_f^2}(\mathbf{x}_S)))$$

$$q_{\phi}(\mathbf{z} | \mathbf{f}, \mathbf{x}) = \mathcal{N}(\mathbf{z} | g_{\mu_z}(\mathbf{f}, \mathbf{x}), \text{diag}(g_{\sigma_z^2}(\mathbf{f}, \mathbf{x})))$$


where $\mathbf{x}_S = (x_{s_1}, \dots, x_{s_N}), N = 3$

Details




Results

Learned dynamic data manifold of the 2d latent space



Naive emotion detection in a 2d latent space



- Digits and style of the handwritten numbers are consistent over the spanned latent space
- Coherence of the dynamic space between different identities

- Two-dimensional latent space captures dynamics of faces
- Naive analysis of the dynamic plot can already extract some meaningful facial expressions (smiling / astonished)